

# SCHÄFER Lochbleche vom Lager:

Lochbild DIN-Bezeichnung	Dicke (s) in mm / 1000 mm x 2000 mm							Dicke (s) in mm / 1250 mm x 2500 mm							Dicke (s) in mm / 1500 mm x 3000 mm							
	0,50	0,75	0,88	1,00	1,50	2,00	3,00	0,50	0,75	0,88	1,00	1,50	2,00	3,00	0,50	0,75	0,88	1,00	1,50	2,00	3,00	
Stahlblech kaltgewalzt DC 01	Rv 1,00 - 2,00			○																		
	Rv 1,50 - 2,50			○																		
	Rv 1,60 - 3,00			○																		
	Rv 2,00 - 3,50			○																		
	Rv 2,50 - 4,00			○																		
	Rv 3,00 - 5,00			○							○											
	Rv 4,00 - 6,00			○							○											
	Rv 5,00 - 8,00			○							○											
	Rv 6,00 - 9,00			○																		
	Rv 8,00 - 11,00			○																		
	Rv 10,00 - 15,00			○							○											
Rg 4,50 - 15,00			○							○												
Qg 5,00 - 7,50			□																			
Qg 5,00 - 8,00			□							□												
Qg 6,00 - 9,00			□																			
Qg 8,00 - 10,00			□							□												
Qg 8,00 - 12,00			□							□							□					
Qg 10,00 - 12,00			□																			
Qg 10,00 - 14,00			□																			
Qg 10,00 - 15,00			□							□							□					
Stahlblech warmgewalzt DD 11	Rv 2,00 - 3,50				○																	
	Rv 3,00 - 5,00				○	○					○											
	Rv 4,00 - 6,00				○	○						○										
	Rv 5,00 - 8,00				○	○	○					○	○								○	
	Rv 6,00 - 9,00				○																	○
	Rv 8,00 - 11,00				○	○																
	Rv 10,00 - 15,00				○	○	○															○
	Rg 4,50 - 15,00				○								○									
	Rg 4,50 - Euro				○								○									
	Qg 5,00 - 7,50				□								□									
	Qg 5,00 - 8,00				□	□							□						□			
Qg 8,00 - 10,00				□																		
Qg 8,00 - 12,00				□	□							□	□									
Qg 10,00 - 12,00				□																		
Qg 10,00 - 14,00				□	□																	
Qg 10,00 - 15,00				□	□	□																

Lochbild DIN-Bezeichnung	Dicke (s) in mm / 1000 mm x 2000 mm							Dicke (s) in mm / 1250 mm x 2500 mm							Dicke (s) in mm / 1500 mm x 3000 mm							
	0,50	0,75	0,88	1,00	1,50	2,00	3,00	0,50	0,75	0,88	1,00	1,50	2,00	3,00	0,50	0,75	0,88	1,00	1,50	2,00	3,00	
Stahlblech feuerverzinkt DX 51 D+Z	Rv 2,00 - 3,50			○																		
	Rv 3,00 - 5,00	○	○		○	○	○		○		○	○						○	○			
	Rv 4,00 - 6,00		○		○	○			○		○							○				
	Rv 5,00 - 7,00		○		○																	
	Rv 5,00 - 8,00	○	○	○	○	○	○		○	○	○	○	○	○					○	○	○	
	Rv 5,00 - 10,00				○							○							○			
	Rv 6,00 - 8,00				○							○										
	Rv 10,00 - 15,00				○	○	○					○	○									
Edelstahl Wst. 1.4301 IIIc	Qg 5,00 - 7,50			□																		
	Qg 5,00 - 8,00			□	□					□												
	Qg 8,00 - 10,00			□	□																	
	Qg 8,00 - 12,00			□	□						□	□										
	Qg 10,00 - 12,00			□							□											
	Qg 10,00 - 14,00			□	□						□											
	Qg 10,00 - 15,00			□	□						□	□	□									
	Rv 3,00 - 5,00			●	●						●											
Rv 4,00 - 6,00			●	●						●												
Rv 5,00 - 8,00			●	●	●					●												
Rv 10,00 - 15,00			●	●																		
Aluminium Al/Mg 3-hh	Rv 3,00 - 5,00			○	○						○											
	Rv 4,00 - 6,00			○							○											
	Rv 5,00 - 8,00			○	○	○					○	○	○					○	○			
	Rv 3,00 - 5,00			○	○																	
Rv 5,00 - 8,00			○	○																		